



RECOMMENDED P.C.B. LAYOUT  
UNSPECIFIED TOLERANCE:±0.05  
(TOP VIEW)

- SPECIFICATION:
- 1.Rating : DC 20V 3A;
  - 2.Contact resistance: ≤50mΩ;  
After test: ≤100mΩ
  - 3.Insulation resistance: ≥100MΩ (DC500V);  
After test: ≥50MΩ
  - 4.Withstand voltage: 500VAC ;
  - 5.Insertion and extraction force: 3-30N;
  - 6.Life test: 5,000 cycles;
  - 7.Operation temperature range:-20°C~70°C;
  - 8.Preservative temperature range:-40°C~85°C;

Model No.	H	J	K
CENTER PIN	ø2.0	ø2.5	ø3.0
DIM A	ø6.3±0.05	ø6.3±0.05	ø6.55±0.05
DIM B	ø2.05 <sup>+0.10</sup> <sub>-0.00</sub>	ø2.55 <sup>+0.10</sup> <sub>-0.00</sub>	ø3.05 <sup>+0.10</sup> <sub>-0.00</sub>

设计:	Arvin: 2016.03.08	范围 Range	公差 Tolerance
审核:	Arvin:	X.X ±	X.X ±0.30
校对:	Ru yi:	X.XX ±	X.XX ±0.20
比例:	视角关系:	X.XXX ±	X.XXX ±0.10
版次:	图框大小: A4	Angle ±	Angle ±5°

东莞市恒祺电子科技有限公司

名称:DC插座      型号: DC-062

料号:

共 张 , 第 张

备注: